



ANDISHEH MEHRARAE SEPAHAN
TECHNICAL DATASHEET
(SOLVENT NAPHTA 150)

Item	Unit	Method	Min	Max	Typical Value
Density @ 15°C	gr/mL	ASTM D 4052	0.88	0.9	0.888
Specific gravity @15.86/15.56	-	ASTM D 4052	0.88	0.9	0.886
Apperance	-	Visual	--	-	Clear and transparent
Distillation					
IBP	°C	ASTM D86	174	185	175
10%	°C	ASTM D86	176	186	178
20%	°C	ASTM D86	179	186	180
30%	°C	ASTM D86	180	186	182
40%	°C	ASTM D86	182	186	184
50%	°C	ASTM D86	184	188	186
60%	°C	ASTM D86	185	189	187
70%	°C	ASTM D86	188	191	190
80%	°C	ASTM D86	192	196	195
90%	°C	ASTM D86	196	203	202
95%	°C	ASTM D86	215	222	220
Dry point	°C	ASTM D86	220	226	225
Aromatic content	wt%	UOP 744-86	98	99.5	99.3
Benzene	wt%	UOP 744-86	0.005	0.010	0.001
C8Aromatics	wt%	UOP 744-86	0.01	0.1	0.03
C9Aromatics	wt%	UOP 744-86	10	30	28
C10Aromatics	wt%	UOP 744-86	65	85	71
Flashpoint	°C	-	60		62
Water content	ppm	-	50	100	20

Packaging: Bulk and drum



Address: No 1. Honar Alley, Meisami St, Keshavarzi Highway
Phone: +98-31-37756695,37752442
Cell: +98-913-601-4287
Email: Andisheh.mas@gmail.com

